



SEGA OF AMERICA, INC.
Consumer Products Division

Rex Sabio
242

32X Sample Disk

Doc. #MAR-40-072094

© 1994 SEGA. All Rights Reserved.

CONFIDENTIAL

PROPERTY OF SEGA

About the Super 32X Sample File

Files are compressed by LHA and EXE.

After being expanded, a WAV file is converted to the S28 file if sound.bat is executed within directory ¥MD. The file is active when the following five files are loaded.

```
md¥loder¥demo. s28
md¥loder¥datatbl. s28
md¥loder¥after.a28
sh¥object¥samp_m. s28
sh¥object¥samp_s. s28
```

The 68000 assembler uses a 2500 AD cross-assembler.

The SH assembler uses an assembler provided by SEGA.

Further, the "make" within md.asm, sh.asm can use the Turbo C as well as Borland C make.

In connection, if the WAV file and data at the end of datatbl.asm are changed, various WAV files can be reproduced.

NOTE:

The sample file on the next page follows the limitations and precautions in June 1994. The latest manual has priority concerning restrictions.

The contents of ICD_MARS.PRG and ICD.MARS.CD as well as their method of use are supported, but the contents of other source files are subject to support.

icd_mars.doc

- ICD_MARS.PRG
Initial program for cartridge ROM.
- ICD_MARS.CD
Initial program for CD.

When cartridge ROM software is created, ICD_MARS.PRG must be included.
Fix ORG = 400H within ICD_MARS.PRG.

A bug that caused the frame buffer occurring in ICD_MARS.PRG of the development board version 1.X to clear improperly and a bug that allowed operation only in the Japan mode are being corrected.

Unconfirmed portions of ICD_MARS.CD still existed as of now (6/94). Should there be any issues, please contact the Technical Support Department.

Rex Sabio
242